

TECHNOLOGY

HOLYKELL®

UE3002
LEVEL
• DATASHEET •


- 1. Pressure Measurement 2. Level Measurement 3. Temperature Measurement**
4. Flow Measurement 5. Display & Control Instruments
6. Wireless Monitoring System 7. Velocity Measurement

UE3002

Ultrasonic Distance/Level Sensors


Profiles

(Unit: mm)



UE3002 Ultrasonic Level Sensor combines ultrasonic sensors, temperature sensors, ultrasonic servo circuit, transmission circuit and uses SMD components and ASIC which is developed together with the United States partner. All these features realize a concise and smart level transmitter. All gold-plated circuit boards, internal electromagnetic shielding and software digital filter are tested for (industrial) 48 hour under high and low temperature aging. It promises higher and long-term reliability. Shell is made of solid texture and good NLEPF acoustic characteristics of synthetic material. The body is shape sophisticated aesthetics, waterproof, dust-proof, and can adapt to the most of working conditions on site. A very quick and easy installation, maintenance can be realized.

Installation



E --- The total face height of container to the sensor, that is the actual installation height;

D --- The height of the sensor to the surfaces of level.

H --- That is the actual level height

Specification

Parameter	UE3002			
Level Range	0-1m 0-2m optional			
Blind area	6cm~15cm			
Beam angle	<6°			
Accuracy	<1.5mm			
Output	Voltage	Current	Serial port	Switch signal
	1~5V;1~10V	4 ~ 20mA 0 ~ 20mA (loading big than 300 ohm)	RS485 (Modbus)	PNP, NPN, Relay output optional (Max 2 channels)
Power supply	DC12-24V/50mA			
Consumption	<1.5W			
Min. resolution	1mm			
Frequency	20 KHz~250KHz			
Protection class	IP65 (default); IP67, IP68 (customized!)			
Operating temp.	-20°C ~60°C			
Housing	ABS/ Nylon			
Cable	User defined (with connectors)			
Dimension	Φ41mm x 106mm x M30			
Installation	M30*1.5 male thread			

Wiring connection

Electronic Wires Connection		
Current	Red	Vcc+
	Yellow	Signal+
Voltage	Red	Vcc+
	Yellow	Signal+
	Black	GND
RS485	Red	Vcc+
	Yellow	RS485A
	White	RS485B
	Black	GND

How to Order

Part Number Selection Table

UE3002 Selection Type	02	A	U1	A2	T1	002
Range	01= 1 Meter 02= 2 Meters					
Water Proof	A= IP66 B= IP65 C= IP67 D=IP68					
Power Supply	U1=DC12V/50mA U2=DC24V/50mA					
Output	A1=Current Output (0-20mA 2 wires) A2=Current Output (4-20mA 2 wires) A3=Current Output (4-20mA 3 wires) A4=Current Output (4-20mA 4 wires) N1/N2=Switch output (1 or 2 switches) V2= Voltage output (1-5V) V4= Voltage output (1-10V) R=Digital RS485(MCU Protocol) X=By Customized					
Temperature	T= 0...50 °C T1= -10...60 °C T2= -20...70 °C					
Cable length	001= 1 Meter	002= 2 Meters	X= By Customized			

Application

